

Battery Powered Automatic PET & PP Combination Strapping Tool

LATEST TECHNOLOGY

- Brushless motor-ZAPAK patented single motor design provides extremely long service life.
- ZAPAK Li-Ion battery- 18Vx 4.0/5.0Ah rechargeable battery with smart Charge Level Indicator (CLI)
- ZAPAK charger (50 ~ 60 minutes)

POWERFUL & SPEEDY

- Max. tension 400 KGS (4000N) - ZP97A heavy duty model.
- Max. tension 250 KGS (2500N) - ZP93B standard duty model.
- Patented new strap grippers design contributes to high tension ability and strap quality tolerance.
- Single-handed operation performs automatic tensioning, friction welding and cutting efficiently.

SAFETY

- Single-handed operation conforms to CE safety directive and meets RoHS requirements.
- Li-Ion battery complies with UN38.3 safety requirements.



SMART & EASY

- Pre-programmed touch panel with digital signal to suit different operation needs instinctively.
- Lightest model in same class of tools approx. 3.4kg (7.5lbs incl. battery) relieves operation fatigue.
- Special tool retreating device ensures smooth and easy removal of tool.
- Unique rear-end roller design prevents scratches or worn out damages on strapping objects.
- User self-adjustable strap widths guiders and self-changeable wearing parts.
- Optional hanger reduces operation fatigue.
- ZP93B Soft mode tension available for slow and low tension on strapping light or fragile objects.

SPECIFICATIONS

Model No.	Description	Fits	Strap Width		Strap Thickness		Tension	Sealing
		Poly-strap	mm	Inch	mm	Inch	Range	Efficiency
BP-ZP93A	1/2" & 5/8" PET & PP Battery Operated Tool w/ 2 Batteries & 1 Charger	PP&PET	12-16	1/2-5/8	0.65-1.05	.026-.04	25-250 kgs (55-550 lbs)	85±5%
BP-ZP97A	5/8" & 3/4" PET & PP Battery Operated Tool w/ 2 Batteries & 1 Charger	PP&PET	16&19	5/8&3/4	0.70-1.05	.028-.04	40-400 kgs (88-880 lbs)	

REMARKS:

Tension performance and Sealing efficiency varies based on strap specification, quality, setting and remaining battery power. Pre-testing before operation is required.